

Lobby Storage Cabinets (2008 NYC Building Code)

Storage cabinets and equipment designed to meet requirements of section 905.3.1 of NYC Building Code 2008. Each cabinet is constructed of 20 gauge cold rolled steel with a white powder coat finish. Standard available trim styles are 3/8" recessed and surface mounted. Fire rated option (mineral wool insulation) is UL Listed for one and two hour combustible and non-combustible wall system building codes, available for recessed cabinets.

Models NYCLSCR and NYCLSCSM Lobby Storage Cabinets come with a solid door and cylinder lock, a shelf, and are sized to contain NYCLSCEQ comprised of 375' of 1.5" hose furnished in (7) 50' lengths and (1) 25' length, (3) open nozzles, (2) 1.5" spanner wrenches, (2) 2.5" spanner wrenches, and (2) 2.5" by 1.5" non-swivel reducing couplings.

Models NYCKSCR and NYCKSCSM Key Storage Cabinets come with a solid door and Yale lock openable by an FDNY standard key.



NYCLSCRSM with NYCLSCEQ

Cabinet Models & Dimensions

| Part # | Trim Style | Trim Depth | Inside Box | | | Outside Trim | | Wall Opening (Non rated) | | | Wall Opening (Fire Rated) | | |
|----------|------------|------------|------------|----------|-------|--------------|--------|--------------------------|--------|-------|---------------------------|---------|---------|
| | | | A | B | C | E | F | Width | Height | Depth | Width | Height | Depth |
| NYCLSCR | Recessed | 3/8 | 24 | 38 3/4 | 8 | 27 3/8 | 42 1/8 | 25 | 39 3/4 | 7 7/8 | 26 5/16 | 41 1/16 | 8 15/16 |
| NYCLSCSM | Surface | ---- | 27 3/16 | 41 15/16 | 8 1/2 | 27 3/8 | 42 1/8 | ---- | ---- | ---- | ---- | ---- | ---- |
| NYCKSCR | Recessed | 3/8 | 5 1/4 | 5 1/4 | 2 1/2 | 8 1/8 | 8 1/8 | 5 1/2 | 5 1/2 | 3 | ---- | ---- | ---- |
| NYCKSCSM | Surface | ---- | 5 1/4 | 5 1/4 | 2 1/2 | 5 5/16 | 5 5/16 | ---- | ---- | ---- | ---- | ---- | ---- |

All dimensions are in inches.

Cabinet Equipment

| Part # | Description |
|---|--|
| NYCLSCEQ | Equipment for NYCLSCR and NYCLSCSM Cabinets |
| Qty | Component Part # |
| Each Set of Equipment Includes the following: | |
| 7 | HSERH50-NYFDB 1.5" x 50' Rack Hose w/ Brass Couplings NYFD |
| 1 | HSERH25-NYFDB 1.5" x 25' Rack Hose w/ Brass Couplings NYFD |
| 3 | 1875NYFDPL 1.5" x 10" Red Polycarbonate Straight Stream Nozzle NYFD - 1/2" Orifice |
| 2 | SPANNERPL15 Spanner Wrench for 1.5" Pin Lugs |
| 2 | SPANNERPL25 Spanner Wrench for 2.5" Pin Lugs |
| 2 | 327NYFD 2.5" F NYFD x 1.5" M NYFD Rough Brass Pin Lug Reducer |

