

## Lobby Storage Cabinets (2014 NYC Building Code)

Storage cabinets and equipment designed to meet requirements of section 905.3.1 of NYC Building Code 2014. Each cabinet is constructed of 20 gauge cold rolled steel with a white powder coat finish, and solid door with Yale lock openable by an FDNY standard key. Standard available trim styles are 3/8" recessed and surface mounted. Fire rated option (mineral wool insulation) is UL Listed for one and two hour combustible and non-combustible wall system building codes, available for recessed cabinets.

Models NYCS2626R and NYCS2626SM are sized to contain NYCS2626EQ comprised of 125' of 1.5" hose furnished in (2) 50' lengths and (1) 25' length, (1) 1.5" spanner wrench, (1) 2.5" spanner wrench, (1) 2.5" by 1.5" non-swivel reducing coupling, and (1) 1.5" polycarbonate adjustable fog nozzle.

Models NYCS1818R and NYCS1818SM are designed for R-2 occupancies in which the hose can be omitted, and are sized to contain (1) 1.5" spanner wrench, (1) 2.5" spanner wrench, (1) 2.5" by 1.5" non-swivel reducing coupling, and (1) 1.5" polycarbonate adjustable fog nozzle.

One set of equipment is to be stored in each cabinet when serving one standpipe riser, and two sets of equipment are to be stored in each cabinet when serving two or more risers. Select cabinet model, corresponding equipment, and sets of equipment below.



NYCS1818R

## Cabinet Models & Dimensions

| Part #     | Trim Style | Trim Depth | Inside Box |         |        | Outside Trim |        | Wall Opening (Non rated) |        |       | Wall Opening (Fire Rated) |         |          |
|------------|------------|------------|------------|---------|--------|--------------|--------|--------------------------|--------|-------|---------------------------|---------|----------|
|            |            |            | A          | B       | C      | E            | F      | Width                    | Height | Depth | Width                     | Height  | Depth    |
| NYCS1818R  | Recessed   | 3/8        | 18         | 18      | 8      | 21 3/8       | 21 3/8 | 19                       | 19     | 7 7/8 | 20 5/16                   | 20 5/16 | 8 15/16  |
| NYCS1818SM | Surface    | ----       | 21 3/16    | 21 3/16 | 8 1/2  | 21 3/8       | 21 3/8 | ----                     | ----   | ----  | ----                      | ----    | ----     |
| NYCS2626R  | Recessed   | 3/8        | 26         | 26      | 10     | 29 3/8       | 29 3/8 | 27                       | 27     | 9 7/8 | 28 5/16                   | 28 5/16 | 10 15/16 |
| NYCS2626SM | Surface    | ----       | 29 3/16    | 29 3/16 | 10 1/2 | 29 3/8       | 29 3/8 | ----                     | ----   | ----  | ----                      | ----    | ----     |

All dimensions are in inches.

## Cabinet Equipment

| Part #            |                  | Description                                     |   |
|-------------------|------------------|---|---|
| NYCS1818EQ        |                  | Equipment for NYCS1818R and NYCS1818SM Cabinets |   |
| One               | Two ←            | SELECT # of RISERS/SETS OF EQUIPMENT            |   |
| Qty (Per Cabinet) | Component Part # |   |   |
| 1                 | 2                | SPANNERPL15                                     | Spanner Wrench for 1.5" Pin Lugs                      |
| 1                 | 2                | SPANNERPL25                                     | Spanner Wrench for 2.5" Pin Lugs                      |
| 1                 | 2                | 327NYFD   | 2.5" F NYFD x 1.5" M NYFD Rough Brass Pin Lug Reducer |
| 1                 | 2                | 1575NYFD  | 1.5" Red Polycarbonate Adjustable Fog Nozzle NYFD     |
| NYCS2626EQ        |                  | Equipment for NYCS2626R and NYCS2626SM Cabinets |   |
| One               | Two ←            | SELECT # of RISERS/SETS OF EQUIPMENT            |   |
| Qty (Per Cabinet) | Component Part # |   |   |
| 2                 | 4                | HSEH50-NYFDB                                    | 1.5" x 50' Rack Hose w/ Brass Couplings NYFD          |
| 1                 | 2                | HSEH25-NYFDB                                    | 1.5" x 25' Rack Hose w/ Brass Couplings NYFD          |
| 1                 | 2                | SPANNERPL15                                     | Spanner Wrench for 1.5" Pin Lugs                      |
| 1                 | 2                | SPANNERPL25                                     | Spanner Wrench for 2.5" Pin Lugs                      |
| 1                 | 2                | 327NYFD   | 2.5" F NYFD x 1.5" M NYFD Rough Brass Pin Lug Reducer |
| 1                 | 2                | 1575NYFD  | 1.5" Red Polycarbonate Adjustable Fog Nozzle NYFD     |

