

## Valve Cabinets

Designed to hold fire hose valves (and extinguishers on some models). Doors are flush with a 5/8" door stop and are attached by a continuous hinge. Standard hardware includes a zinc plated handle and roller catch.



### Door and Frame Material

Select Door & Frame Material

#### Standard

Cold rolled steel with white powder coat finish, 20 gauge.


#### Optional

- **AL** Aluminum with a clear anodized finish, 18 gauge. Surface mounted models have square edge trim and clear anodized aluminum tubs. All other models have a cold rolled steel tub with a powder coated finish.
- **SS** Stainless steel type 304 with a #4 finish, 20 gauge. Surface mounted models have rolled edge trim and stainless steel tubs with a galvanized rear panel. All other models have a cold rolled steel tub with a powder coated finish.


### Door Style

Select Door Style


- **F** Full Glazing
- **S** Solid
- **D** Horizontal Duo
- **V** Vertical Duo




Full Glazing



Solid



Horizontal Duo



Vertical Duo

### Door Glazing (if not solid door)

Select Glazing

#### Standard

- **10** Clear Acrylic

#### Optional

- **13** Wire Glass w/ Safety Film
- **15** Bronze Acrylic
- **16** Gray Acrylic
- **17** Clear Tempered Glass
- **18** Laminated Safety Glass

### Options

Select Options

- **FX2 Fire Rating** - Fabricated in accordance with the UL label for 1 and 2 hour combustible and non-combustible wall system building codes. Utilizes Firespan™ 90 by Thermafiber®, a lightweight, foil-faced mineral wool insulation.
- **L Lock** - Keyed cylinder lock to deter theft or vandalism. Designed to be opened with a sharp pull that breaks the replaceable plastic cam, allowing quick access in the event of an emergency.
- **D Die Cut Lettering** - Offers cabinet identification. Specify color (red, black, or white) and orientation (horizontal or vertical).

## Models & Dimensions

\* All dimensions are in inches. \* Knockouts are not available on stainless steel or fire-rated cabinets.  
 \* Add 5/8" to depth of wall opening required for aluminum cabinets.

Part #	Trim Style	Trim Depth	Inside Box			Outside Trim		Knockout Locations			Wall Opening (Non-rated)			Wall Opening (Fire Rated)			Recommended Interior Capacity
			A	B	C	E	F	J	G	K	Width	Height	Depth	Width	Height	Depth	
JL8515	Recessed	3/8	18	18	8	21 3/8	21 3/8	4	9	2 1/2	19	19	7 7/8	20 5/16	20 5/16	8 15/16	(1) 2 1/2" angle hose valve w/ cap
JL8516	Semi-recessed	1 1/4	18	18	8	21 3/8	21 3/8	4	9	2 1/2	19	19	6 7/8	20 5/16	20 5/16	7 15/16	
JL8517	Semi-recessed	2 1/2	18	18	8	21 3/8	21 3/8	4	9	2 1/2	19	19	5 5/8	20 5/16	20 5/16	6 11/16	
JL8514	Trimless	---	18	18	8	20 1/2	20 1/2	4	9	4	19	19	8 1/8	20 5/16	20 5/16	8 11/16	
JL8513	Surface	---	21 3/16	21 3/16	8 1/2	21 3/8	21 3/8	---	---	---	---	---	---	---	---	---	
JL8415	Recessed	3/8	18	18	10	21 3/8	21 3/8	5	9	5	19	19	9 7/8	20 5/16	20 5/16	10 15/16	(1) 2 1/2" angle hose valve w/ reducer and cap
JL8416	Semi-recessed	1 1/4	18	18	10	21 3/8	21 3/8	5	9	5	19	19	8 7/8	20 5/16	20 5/16	9 15/16	
JL8417	Semi-recessed	2 1/2	18	18	10	21 3/8	21 3/8	5	9	5	19	19	7 5/8	20 5/16	20 5/16	8 11/16	
JL8414	Trimless	---	18	18	10	20 1/2	20 1/2	5	9	5	19	19	10 1/8	20 5/16	20 5/16	10 11/16	
JL8413	Surface	---	21 3/16	21 3/16	10 1/2	21 3/8	21 3/8	---	---	---	---	---	---	---	---	---	
JL8715	Recessed	3/8	26	26	8	29 3/8	29 3/8	4	13	4	27	27	7 7/8	28 5/16	28 5/16	8 15/16	(1) 2 1/2" angle hose valve w/ cap
JL8716	Semi-recessed	1 1/4	26	26	8	29 3/8	29 3/8	4	13	4	27	27	6 7/8	28 5/16	28 5/16	7 15/16	
JL8717	Semi-recessed	2 1/2	26	26	8	29 3/8	29 3/8	4	13	4	27	27	5 5/8	28 5/16	28 5/16	6 11/16	
JL8714	Trimless	---	26	26	8	28 1/2	28 1/2	4	13	4	27	27	8 1/8	28 5/16	28 5/16	8 11/16	
JL8713	Surface	---	29 3/16	29 3/16	8 1/2	29 3/8	29 3/8	---	---	---	---	---	---	---	---	---	
JL8615	Recessed	3/8	26	26	10	29 3/8	29 3/8	5	13	5	27	27	9 7/8	28 5/16	28 5/16	10 15/16	(1) 2 1/2" angle hose valve w/ reducer and cap
JL8616	Semi-recessed	1 1/4	26	26	10	29 3/8	29 3/8	5	13	5	27	27	8 7/8	28 5/16	28 5/16	9 15/16	
JL8617	Semi-recessed	2 1/2	26	26	10	29 3/8	29 3/8	5	13	5	27	27	7 5/8	28 5/16	28 5/16	8 11/16	
JL8614	Trimless	---	26	26	10	28 1/2	28 1/2	5	13	5	27	27	10 1/8	28 5/16	28 5/16	10 11/16	
JL8613	Surface	---	29 3/16	29 3/16	10 1/2	29 3/8	29 3/8	---	---	---	---	---	---	---	---	---	
JL8015	Recessed	3/8	16	40	9	19 3/8	43 3/8	4 1/4	6	4 1/4	17	41	8 7/8	18 5/16	42 5/16	9 15/16	(1) 2 1/2" angle hose valve w/ cap + (1) fire extinguisher
JL8016	Semi-recessed	1 1/4	16	40	9	19 3/8	43 3/8	4 1/4	6	4 1/4	17	41	8 1/8	18 5/16	42 5/16	8 15/16	
JL8017	Semi-recessed	2 1/2	16	40	9	19 3/8	43 3/8	4 1/4	6	4 1/4	17	41	6 5/8	18 5/16	42 5/16	7 11/16	
JL8014	Trimless	---	16	40	9	18 1/2	42 1/2	4 1/4	6	4 1/4	17	41	9 1/8	18 5/16	42 5/16	9 11/16	
JL8013	Surface	---	19 3/16	43 3/16	9 1/2	19 3/8	43 3/8	---	---	---	---	---	---	---	---	---	

- All 16" x 40" cabinets come standard with a heavy duty shelf located 12" up from the bottom for supporting a fire extinguisher. The shelf can be deleted at no additional cost.

