



90° Pattern

Female dry hydrants are used when fire departments are using large diameter fire hose equipped with NST threaded couplings. Female dry hydrants are designed for use in rural areas with ponds, lakes, and streams so water can be drawn out of them in emergency situations.

- Light-weight 6061-T6 aluminum alloy on connectors
- schedule 40 standard PVC for the piping
- 90° PVC Elbow and 45° PVC Elbow configurations
- Straight PVC pipe configurations also available
- 4½" NST, 5" NST, and 6" NST options
- Equipped with internal debris screen



45° Pattern



Straight Pattern



No PVC

Part #	Configuration	Size
DHF45LPVC	No PVC	4½" Female NST x 6" F NPSH w/ cap & chain.
DHF5LPVC	No PVC	5" Female NST x 6" F NPSH w/ cap & chain.
DHF6LPVC	No PVC	6" Female NST x 6" F NPSH w/ cap & chain.
DHF45180	Straight Pattern	4½" Female NST w/ cap & chain x 6" straight PVC
DHF5180	Straight Pattern	5" Female NST w/ cap & chain x 6" straight PVC
DHF6180	Straight Pattern	6" Female NST w/ cap & chain x 6" straight PVC
DHF4545	45°	4½" Female NST w/ cap & chain x 6" 45° PVC Elbow
DHF545	45°	5" Female NST w/ cap & chain x 6" 45° PVC Elbow
DHF645	45°	6" Female NST w/ cap & chain x 6" 45° PVC Elbow
DHF4590	90°	4½" Female NST w/ cap & chain x 6" 90° PVC Elbow
DHF590	90°	5" Female NST w/ cap & chain x 6" 90° PVC Elbow
DHF690	90°	6" Female NST w/ cap & chain x 6" 90° PVC Elbow