

2-Way and 3-Way Roof Manifolds

Designed for use as a roof manifold or hydrant, these bodies act as an auxiliary outlet for the fire department.

May also be used as a test header to flow test a fire pump or backflow preventer.

250 GPM per outlet.

Standard finish: Rough Brass







RM222-01

Straight Bodies

Part #	Туре	Size	Outlet	Α	В	С
RM221-01	2-Way	4" F NPT x (2) 21/2" Male	NPT	6¾"	4 7/8"	5"
RM221-13	2-Way	4" Groove x (2) 21/2" Male	NPT	6¾"	6½"	4½"
RM221-04	2-Way	4" F NPT x (2) 21/2" Male	NST	6¾"	4 7/8"	5"
RM221-07	2-Way	6" F NPT x (2) 21/2" Male	NPT	81/4"	6 3/8"	7 5/8"
RM221-10	2-Way	6" F NPT x (2) 2½" Male	NST	81/4"	6 3/8"	7 5/8"
RM231-01	3-Way	4" F NPT x (3) 21/2" Male	NPT	12¾"	83/4"	5¼"
RM231-03	3-Way	6" F NPT x (3) 21/2" Male	NPT	15 3/8"	9¾"	7 5/8"
RM231-04	3-Way	6" F NPT x (3) 2½" Male	NST	15 3/8"	9¾"	7 5/8"


Specify Finish:


-RB Rough Brass

-PB Polished Brass

-PC Polished Chrome

• RM221-13 Available in rough brass only





90° Bodies

Part #	Туре	Size	Outlet	Α	В	С
RM222-01	2-Way	4" F NPT x (2) 2½" Male	NPT	6 7/8"	71/4"	5"
RM222-06	2-Way	4" Groove x (2) 21/2" Male	NPT	7½"	71/4"	4 1/2"
RM222-04	2-Way	4" F NPT x (2) 2½" Male	NST	6 7/8"	71/4"	5"
RM222-07	2-Way	6" F NPT x (2) 2½" Male	NPT	9"	81/2"	7 1/2"
RM222-10	2-Way	6" F NPT x (2) 2½" Male	NST	9"	81/2"	7 1/2"
RM232-01	3-Way	4" F NPT x (3) 2½" Male	NPT	6 3/8"	9"	7"
RM232-03	3-Way	6" F NPT x (3) 2½" Male	NPT	6 3/8"	10½"	7 1/2"
RM232-04	3-Way	6" F NPT x (3) 2½" Male	NST	6 3/8"	10½"	7 1/2"

Specify Finish:

-RB Rough Brass

-PB Polished Brass

-PC Polished Chrome

• RM222-06 Available in rough brass only

