

Halotron

Halotron is a clean, non conductive gaseous agent that is an excellent replacement for Halon 1211 extinguishers. Also, unlike traditional dry chemical extinguishers, which can be corrosive, Halotron I is a clean agent that leaves zero residue after use, and consequently causes little to no collateral damage on equipment in the proximity of the fire.

Halotron is suitable for use on Class A, Class B, and Class C fires.

- **Class A** - Ordinary combustibles: wood, paper, rubber, fabrics, and many plastics
- **Class B** - Flammable liquids & gases: gasoline, oils, paint, lacquer and tar
- **Class C** - Fires involving live electrical equipment

Specifications:

- UL & ULC Listed
- Aluminum valve
- Wall mount included
- Rechargeable
- USA made



Part #	EXT25HAL	EXT25HALV	EXT5HAL	EXT5HALV	EXT11HAL	EXT155HAL
Mfg. part #	70259	70256	75550	75555	71100	71550
Agent Capacity	2½ lb.	2½ lb.	5 ½ lb.	5 lb.	11 lb.	15½ lb.
UL/ULC Rating	2-B:C	2-B:C	5-B:C	5-B:C	1-A:10-B:C	2-A:10-B:C
Temperature Range	-40° to 120° F					
Discharge Time	9 Sec.	9 Sec.	9 Sec.	9 Sec.	9 Sec.	13 Sec.
Discharge Range (ft.)	6 - 10 feet	6 - 10 feet	9 - 15 feet	9 - 15 feet	9 - 15 feet	12 - 18 feet
Operating Pressure	100 PSI	100 PSI	100 PSI	100 PSI	100 PSI	125 PSI
Mounting Type	Wall	Vehicle	Wall	Vehicle	Wall	Wall
USCG Approval	N/A	N/A	N/A	Type B:C Size I	Type B:C Size I	Type B:C Size II
Ship Weight	5½ lb.	5½ lb.	10 lb.	10¼ lb.	21¼ lb.	25¾ lb.
Unit Height	13.375"	13.375"	16.375"	16.375"	17½"	17½"
Unit Width	6.75"	5.625"	7¼"	7¼"	8.625"	8.625"
Unit Diameter	3.375"	3.375"	4¼"	4¼"	7"	7"