

Our double jacket fire hose is manufactured in accordance with NFPA standard, current edition. The polyester construction is mildew and rot-proof.

Double jacket fire hose is typically used for municipal attack line, supply line, industrial fire fighting, master stream appliance, and crash/fire rescue use due to its 400PSI service pressure rating.

- 100% high tenacity polyester jacket
- EPDM rubber lined
- 400 PSI service pressure - 800 PSI test pressure
- Standard color: White
- Additional colors also available
- Standard coupling material: Aluminum
- Optional coupling material: Brass
- Standard coupling thread spec: NST (hose thread)
- Optional coupling thread spec for 1½" and 1¾": NPSH (pipe thread)
- Not recommended for low flow nozzles



Part #	Size
HSE15-25DJ	1½" x 25'
HSE15-5DJ	1½" x 50'
HSE15-75DJ	1½" x 75'
HSE15-1DJ	1½" x 100'
HSE175-5DJ	1¾" x 50'
HSE175-1DJ	1¾" x 100'
HSE25-25DJ	2½" x 25'
HSE25-5DJ	2½" x 50'
HSE25-75DJ	2½" x 75'
HSE25-1DJ	2½" x 100'
HSE3-25DJ	3" x 25'
HSE3-5DJ	3" x 50'
HSE3-1DJ1	3" x 100'

Specify Coupling Material:

-Aluminum (Standard)

-B Brass

Specify Thread Type:

-1 NST (Standard)

-3 NPSH (1½" and 1¾" only)