

Flush Mount Inlets (Clappered)

Used by the fire department to supply additional water to a building's fire protection system. These flush mounted units are generally concealed behind the outside wall of the building. Bodies are constructed of cast brass.

250 GPM per inlet, each inlet features individual drop clapper. 250 PSI max operating pressure. U/L Listed. FDNY Approved. Contact us for current approvals.



FDC121-033

Part #	Size	Outlet Type	Inlet Type	Outlet Location	A	B	C	D
FDC121-013	4" x 3" x 3"	Female NPT	Female NPT	Back	11 13/16"	7 1/4"	7 5/8"	5 3/16"
FDC122-013	4" x 3" x 3"	Female NPT	Female NPT	Bottom	11 13/16"	6 1/4"	7 5/8"	7 1/16"
FDC123-013	4" x 3" x 3"	Female NPT	Female NPT	Top	11 13/16"	6 1/4"	7 5/8"	7 1/16"
FDC121-033	4" x 3" x 3"	Groove	Female NPT	Back	11 13/16"	7 13/16"	7 5/8"	5 3/16"
FDC122-033	4" x 3" x 3"	Groove	Female NPT	Bottom	11 13/16"	6 1/4"	7 5/8"	7 1/16"
FDC123-033	4" x 3" x 3"	Groove	Female NPT	Top	11 13/16"	6 1/4"	7 5/8"	7 1/16"
FDC121-023	6" x 3" x 3"	Female NPT	Female NPT	Back	11 13/16"	8 1/4"	7 5/8"	7 1/16"
FDC122-023	6" x 3" x 3"	Female NPT	Female NPT	Bottom	11 13/16"	7 5/16"	7 5/8"	7 1/16"
FDC123-023	6" x 3" x 3"	Female NPT	Female NPT	Top	11 13/16"	7 5/16"	7 5/8"	7 1/16"
FDC121-0233	6" x 3" x 3"	Groove	Female NPT	Back	11 13/16"	8 1/4"	7 5/8"	7 1/16"
FDC122-0233	6" x 3" x 3"	Groove	Female NPT	Bottom	11 13/16"	7 5/16"	7 5/8"	7 1/16"
FDC123-0233	6" x 3" x 3"	Groove	Female NPT	Top	11 13/16"	7 5/16"	7 5/8"	7 1/16"

