

Flush Mount Test Headers (With Valves)

Provide a means to flow test a fire pump. These flush mounted units feature a body that's typically concealed behind a wall with only the plate, valves, and caps exposed.

250 GPM per outlet

- **4" 2-way Standard Equipment:** Units are equipped with a brass concealed body, wall plate, 2½" F NPT x 2½" M NYFD gate valves and 2½" caps.
- **6" 2-way Standard Equipment:** Units are equipped with a brass concealed body, wall plate, 3" F NPT x 2½" M NYFD gate valves (loose bonnet style), and 2½" caps.
- **3-way, 4-way, and 6-way Standard Equipment:** Units are equipped with a schedule 40 steel concealed body with 3" grooved outlets, wall plate, 3" F NPT x 2½" M NYFD gate valves (loose bonnet style), and 2½" caps.



520PBPTNYFD

Part #	Type	Size & Configuration	Inlet Type	Inlet Location	A	B	C
520	2-Way	4" x 2½" x 2½"	Female NPT	Back	11½"	6½"	7"
521	2-Way	4" x 2½" x 2½"	Female NPT	Top / Bottom	12"	5½"	7"
520G	2-Way	4" x 2½" x 2½"	Groove	Back	11½"	6½"	7"
521G	2-Way	4" x 2½" x 2½"	Groove	Top / Bottom	12"	5½"	7"
522	2-Way	6" x 2½" x 2½"	Female NPT	Back	11½"	7½"	7 5/8"
523	2-Way	6" x 2½" x 2½"	Female NPT	Top / Bottom	12"	9½"	7 5/8"
522G	2-Way	6" x 2½" x 2½"	Groove	Back	11½"	7½"	7 5/8"
523G	2-Way	6" x 2½" x 2½"	Groove	Top / Bottom	12"	9½"	7 5/8"
530	3-Way	6" x 2½" x 2½" x 2½"	Groove	End	23¼"	8½"	7"
531	3-Way	6" x 2½" x 2½" x 2½"	Groove	Back	19¾"	10½"	7"
532	3-Way	6" x 2½" x 2½" x 2½"	Groove	Top / Bottom	19¾"	8½"	7"
533	3-Way	6" x 2½" x 2½" x 2½"	Female NPT	End	23¼"	8½"	7"
534	3-Way	6" x 2½" x 2½" x 2½"	Female NPT	Back	19¾"	10½"	7"
535	3-Way	6" x 2½" x 2½" x 2½"	Female NPT	Top / Bottom	19¾"	8½"	7"
540	4-Way	6" x 2½" x 2½" x 2½" x 2½"	Groove	End	30¼"	8½"	7"
541	4-Way	6" x 2½" x 2½" x 2½" x 2½"	Groove	Back	26¾"	10½"	7"
542	4-Way	6" x 2½" x 2½" x 2½" x 2½"	Groove	Top / Bottom	26¾"	8½"	7"
543	4-Way	6" x 2½" x 2½" x 2½" x 2½"	Female NPT	End	30¼"	8½"	7"
544	4-Way	6" x 2½" x 2½" x 2½" x 2½"	Female NPT	Back	26¾"	10½"	7"
545	4-Way	6" x 2½" x 2½" x 2½" x 2½"	Female NPT	Top / Bottom	26¾"	8½"	7"
550	4-Way	6" x 2½" x 2½" x 2½" x 2½" (Square)	Groove	Back	14¼"	10½"	7"
551	4-Way	6" x 2½" x 2½" x 2½" x 2½" (Square)	Groove	Top / Bottom	14¼"	8"	7"
560	6-Way	8" x 2½" x 2½" x 2½" x 2½" x 2½" x 2½"	Groove	End	44¼"	9¾"	7"

Specify Finish:

- RB Rough Brass
- PB Polished Brass
- PC Polished Chrome

Specify Orientation:

- Horizontal (standard)
- V Vertical

Specify Wall Plate Lettering:

- WH Wall Hydrant
- PT Fire Pump Test

Hose Threads:

- NYFD

SEE PART DIAGRAMS ON PAGE 2

