

Attachment Hardware

1. **SAF (Seismic Anchoring Fittings)** These fittings have many seismic sway brace applications. The hole in the tab can accommodate our gold, orange, and green cable without a thimble and with bolt hole sizes of 1/4", 3/8", 1/2", 5/8", 3/4", 7/8", 1" & 1 1/4". SAFs may be used as connection fittings for anchorage to structure, or as connection to braced components.
2. **SAFR (Seismic Anchoring Fitting Retrofit)** These fittings are used in the same manner as the SAF, except that they are slotted to permit a hex nut on an existing component to be loosened, the SAFR positioned and the hex nut re-tightened. The SAFR is available for gold and orange cable. All of the bolt hole sizes from 1/4" through 5/8" are available.
3. **Zinc-plated oval sleeves** are the fittings used to secure sizes gold, orange, green, and black seismic cable connections. Loos' Zinc-plated oval sleeves are the only acceptable method to make secure connections to Loos' Seismic Bracing Cable.

Part Number	Size	Notes
SAF-1/4	1/4"	Seismic Anchoring Fitting
SAF-1/2	1/2"	Seismic Anchoring Fitting
SAF-3/8	3/8"	Seismic Anchoring Fitting
SAF-5/8	5/8"	Seismic Anchoring Fitting
SAF-3/4	3/4"	Seismic Anchoring Fitting
SAF-7/8	7/8"	Seismic Anchoring Fitting
SAF-1	1"	Seismic Anchoring Fitting
SAF-1-1/4	1 1/4"	Seismic Anchoring Fitting
SAFR-1/4	1/4"	Seismic Anchoring Fitting Retrofit
SAFR-3/8	3/8"	Seismic Anchoring Fitting Retrofit
SAFR-1/2	1/2"	Seismic Anchoring Fitting Retrofit
SAFR-5/8	5/8"	Seismic Anchoring Fitting Retrofit
GO3-SLV	for Gold cable	Zinc Plated Oval Sleeve
OR4-SLV	for Orange cable	Zinc Plated Oval Sleeve
GR6-SLV	for Green cable	Zinc Plated Oval Sleeve
BL8-SLV	for Black cable	Zinc Plated Oval Sleeve



1. SAF - Seismic Anchoring Fittings



2. SAFR - Seismic Anchoring Fitting Retrofit



3. Zinc Plated Oval Fitting