

## Storz Connections

Typically used as an auxiliary inlet to help supplement a fire protection system's water supply. Enables quick connection of large diameter hose by the fire department to the fire sprinkler or standpipe systems.

Forged and extruded 6061-T6 aluminum.

Rated for up to 250 PSI.

Meets or exceeds NFPA 1963 requirements.

Cap & chain included.



### Specify Finish:

-K Grey Powder Coat (Standard)

-PB Polished Brass

-PC Polished Chrome

\*Brass and chrome only available on 4" x 4", 5" x 4", 4" x 6", and 5" x 6"

### Specify "T" Option for 30° Angle Type:

-T 30° Angled Storz x Rigid NPSH, with 1/2" NPT pipe drop and tee union, 1/2" ball drip valve, 1/2" ball valve with 1/2" x 1/2" pipe nipple.

Part #	Type	Size
SZ25X25	Straight	2½" Storz x 2½" F NPT
SZ4X15	Straight	4" Storz x 1½" F NPT
SZ4X2	Straight	4" Storz x 2" F NPT
SZ4X25	Straight	4" Storz x 2½" F NPT
SZ4X3	Straight	4" Storz x 3" F NPT
SZ4X4	Straight	4" Storz x 4" F NPT
SZ4X6	Straight	4" Storz x 6" F NPT
SZ5X4	Straight	5" Storz x 4" F NPT
SZ5X6	Straight	5" Storz x 6" F NPT
SZ6X6	Straight	6" Storz x 6" F NPT
SZ4X430R	30° Angle	4" Storz x 4" F NPT
SZ4X630R	30° Angle	4" Storz x 6" F NPT
SZ5X430R	30° Angle	5" Storz x 4" F NPT
SZ5X630R	30° Angle	5" Storz x 6" F NPT
SZ6X630R	30° Angle	6" Storz x 6" F NPT
SZ4X490	90° Angle	4" Storz x 4" F NPT
SZ4X690	90° Angle	4" Storz x 6" F NPT
SZ5X490	90° Angle	5" Storz x 4" F NPT
SZ5X690	90° Angle	5" Storz x 6" F NPT
SZ6X690	90° Angle	6" Storz x 6" F NPT
SZ4X4120	120° Angle	4" Storz x 4" F NPSH Swivel
SZ4X6120	120° Angle	4" Storz x 6" F NPSH Swivel
SZ5X4120	120° Angle	5" Storz x 4" F NPSH Swivel
SZ5X6120	120° Angle	5" Storz x 6" F NPSH Swivel

