

Trim Valves

OS&Y Valves - Bronze

Used for monitoring sprinkler systems. The valve stem is visible above the hand wheel when open, and concealed inside the valve body when closed. This allows for immediate visual confirmation that the valve is either "open" or "closed".

Features a bronze body with cast iron hand wheel.

Can be fitted with an external tamper switch (sold by others) for central station or panel monitoring.

Part #	Size
OSY1	1" F NPT x 1" F NPT
OSY125	1¼" F NPT x 1¼" F NPT
OSY15	1½" F NPT x 1½" F NPT
OSY2	2" F NPT x 2" F NPT







Adjustable Pressure Relief Valves

Designed for use in sprinkler systems where pressure relief is required.

Features a diamond knurled adjustment cap for easy adjustment, as well as directional arrows on body for proper flow indication.

Can be adjusted from 75 - 175 PSI. Pressure markings on the adjustment cap are for reference only. An approved sprinkler system pressure gauge must be used for proper relief setting.

Body is cast bronze.

Part #	Size
APRV1/2	1⁄2" NPT



Used to drain water in a plumbing or heating system. Features a cast brass body with cast iron hand wheel. 125 lb. CWP

Part #	Size
BOILERD1/2	1⁄2" M NPT x 3⁄4" M GHT
BOILERD3/4	¾" M NPT x ¾" M GHT



