

Swing Check Valves

Designed to prevent backflow while maintaining full flow and very little turbulence or pressure loss.

Brass construction.

For horizontal installation only.



| Part # | Size |
|---------|-----------------------|
| SWCV1/2 | ½" F NPT x ½" F NPT |
| SWCV3/4 | ¾" F NPT x ¾" F NPT |
| SWCV1 | 1" F NPT x 1" F NPT |
| SWCV125 | 1¼" F NPT x 1¼" F NPT |
| SWCV15 | 1½" F NPT x 1½" F NPT |
| SWCV2 | 2" F NPT x 2" F NPT |

Inline Spring Check Valves

Designed to prevent backflow.

Cast brass construction .

EPDM seat and seal.

Spring loaded, stainless steel spring, opens at 2 PSI.

For both horizontal and vertical installation.



| Part # | Size |
|---------|-----------------------|
| SPCV1/2 | ½" F NPT x ½" F NPT |
| SPCV3/4 | ¾" F NPT x ¾" F NPT |
| SPCV1 | 1" F NPT x 1" F NPT |
| SPCV125 | 1¼" F NPT x 1¼" F NPT |
| SPCV15 | 1½" F NPT x 1½" F NPT |
| SPCV2 | 2" F NPT x 2" F NPT |