

SUBMITTAL: MODEL CT™ FLUSH ACCESS PANELS

PAGE 1 OF 2

Model CT for Acoustic Tile or Drywall Ceilings **NEW HEAVIER CONSTRUCTION STANDARD!**

Sound control and appearance are the important features of Model CT: A covering of acoustical tile or drywall can be inserted into the recessed door panels with exposure of only the narrow frame edges. Acoustical tile or drywall up to 1/2" thick is accommodated by the recessed panel. Attach the tile to the door with adhesive and ensure that it is flush with adjoining tile field. A continuous hinge, located at the outside edge of the door ensures easy opening of the plaster or tile covered panel. Not to be used for suspended ceilings.

SPECIFICATIONS:

Door Panel: 16 gauge steel, recess to accommodate 1/2" for tile or drywall.

Frame: 14 gauge steel

Finish: White powder coat paint.

Hinge: Recessed, continuous hinge mounted on the long side of oblong panels.

Lock: Flush screwdriver-operated steel cam standard "C"

Sizes: Minimum 8" x 8" (203 x 203 mm), maximum 36"x 36"



Panel shown as partially-covered
by acoustic tile



STEP 1: SELECT MODEL NUMBER AND QUANTITY ON CHART

STEP 2: SELECT MATERIAL

- _____ CT Steel
_____ CTG Galvanized (Additional Cost)

Please Note - Color Codes and
Lock Option Codes have
Changed.

STEP 3: SELECT OPTIONAL FEATURES AT ADDITIONAL COST:



- ☐ Optional color Code: _____ - see below
☐ (L) Cylinder lock installed
☐ (C2) Torx head cam
☐ (C4) Hex head cam
☐ (C3) Spanner head cam
☐ (M1) Mortise cam lock prep 1-1/8" dia, 1-3/8" length
☐ (M2) Mortise cam lock (06431) installed
☐ Optional Door Panel Depth (Contact Manufacturer)



Standard
Cam Latch

LATCH AND LOCK OPTIONS

Cylinder Lock (L)	Optional Torx Head Cam (C2)	Optional Spanner Head Cam (C3)	Optional Hex Head Cam (C4)	Mortise Lock (M2)

 JL INDUSTRIES	 CONSTRUCTION PRODUCTS GROUP CT IS A TRADEMARK OF ACTIVAR PLEASE DOWNLOAD MOST CURRENT SUBMITTAL FROM WEBSITE BEFORE ORDERING	Distributor:	Quantity:
		Contractor:	Approved By:
		Model #:	Architect:
		Project:	Date: © Activar Construction Products Inc 2017
HEADQUARTERS: 9702 NEWTON AV S, BLOOMINGTON, MN 55431 PH: 800-554-6077 FAX: 952-835-2218 EMAIL: SALES@ACTIVARCPG.COM WWW.ACTIVARCPG.COM MANUFACTURING: BLOOMINGTON, MN & COMMERCE, CA WAREHOUSES: FT MYERS FL, DALLAS TX, LANCASTER PA, ATLANTA GA, CHICAGO, IL, Seattle WA, Fargo ND, Omaha NE 1/30/2017			

SUBMITTAL: MODEL CT™ FLUSH ACCESS PANELS

PAGE 2 OF 2

QTY	A - MODEL SIZE	B - OUTSIDE FRAME DIMENSIONS		SHIPPING WEIGHT AP-PROX.	LATCH (ES)
	WIDTH X HEIGHT	WIDTH	HEIGHT		
	12" x 12"	12 1/4 "	12 1/4 "	9 lbs	1
	12" x 24"	12 1/4 "	24 1/4 "	14 lbs	2
	18" x 18"	18 1/4 "	18 1/4 "	15 lbs	3
	22" x 30"	22 1/4 "	30 1/4 "	26 lbs	4
	24" x 24"	24 1/4 "	24 1/4 "	24 lbs	4
	24" x 36"	24 1/4 "	36 1/4 "	34 lbs	5
	36" x 36"	36 1/4"	36 1/4"	51 lbs	6

Optional Colors at Additional Cost - Samples Available			
G-Gray	R-Red	BK-Black/FB Flat	SI - Silver
S-Sand	AB-AMS Beige	SB-SC Flat Beige	B-Bronze

