

Carbon Dioxide

Carbon Dioxide is the trusted non-conductive clean agent and is most efficient for dealing with electronic equipment fires. CO₂ is advisable for use on Class B and Class C fires.

- **Class B** - Flammable liquids & gases: gasoline, oils, paint, lacquer and tar
- **Class C** - Fires involving live electrical equipment

Specifications:

- UL & ULC Listed
- Aluminum valve
- Wall mount included
- Rechargeable
- USA Made



Part #	EXT5CO2	EXT10CO2	EXT15CO2	EXT20CO2
Mfg. part #	45100	45600	46100	46600
Agent Capacity	5 lb.	10 lb.	15 lb.	20 lb.
UL/ULC Rating	5-B:C	10-B:C	10-B:C	10-B:C
Temperature Range	-22° to 120°F (-30° to 49°C)			
Discharge Time	9 sec	9 sec	15 sec	20 sec
Discharge Range ft (m)	4-8 feet	4-8 feet	4-8 feet	4-8 feet
Mounting Type	Wall	Wall	Wall	Wall
USCG Approval	Type B:C Size I	Type B:C Size I	Type B:C Size II	Type B:C Size II
Ship Weight	13.75 lb.	27.75 lb.	37.75 lb.	49 lb.
Unit Height	17.375 in	19.75 in	26.375 in	26.875 in
Unit Width	8.25 in	12 in	12 in	13 in
Unit Diameter	5.25 in	6.89 in	6.89 in	8 in