

Wheeled Extinguishers

Wheeled fire extinguishers have your large-scale fire protection needs protected. Available in Dry Chemical (ABC), Halotron (ABC), and Carbon Dioxide (BC) varieties with different size options as well.

Designed for one man operation, these units are easily transportable through doorways and over rough terrain. All models are rechargeable and meet applicable UL requirements. Certain models have US Coast Guard Approval.

- **Class A** - Ordinary combustibles: wood, paper, rubber, fabrics, and many plastics
- **Class B** - Flammable liquids & gases: gasoline, oils, paint, lacquer and tar
- **Class C** - Fires involving live electrical equipment



Part #	Type	Mfg. Part #	Agent Capacity	UL/ULC Rating	Discharge Time	Discharge Range	Unit Weight
EXT50ABCW	ABC Dry Chemical - Stored Pressure	30010	50 lb.	10-A:160-B:C	35 Sec.	25 - 35 feet	154 lbs.
EXT125ABCW	ABC Dry Chemical - Stored Pressure	30110	125 lb.	30-A:240-B:C	47 Sec.	30 - 40 feet	300 lbs.

Part #	Type	Mfg. Part#	Agent Capacity	UL/ULC Rating	Discharge Time	Operating Temperature Range	Range	Unit Weight	H x W x D	Hose Diameter + Length
EXT65HALW	Halotron	76500	65 lb.	4-A:40-B:C	17 Sec.	-40° to 120°F	15 - 25 feet	252 lb.	50" x 24" x 41½"	¾" x 25'
EXT150HALW	Halotron	71500	150 lb.	10-A:80-B:C	23 Sec.	-40° to 120°F	23 - 36 feet	396 lb.	62" x 24" x 41½"	1" x 40'

Part #	Type	Mfg. Part#	Agent Capacity	UL Rating	USCG Approval	Discharge Time	Operating Temperature Range	Range	Unit Weight	H x W x D	Hose Diameter + Length
EXT50CO2W	Carbon Dioxide	35050	50 lb.	20-B:C	Type B:C Size IV	40 Sec.	-22° to 120°F	15 feet	286 lb.	60" x 31" x 21"	½" x 15'
EXT100CO2W	Carbon Dioxide	35100	100 lb.	20-B:C	Type B:C Size V	80 Sec.	- 22° to 120°F	15 feet	416 lb.	65" x 30" x 21"	½" x 40'